

Panafax UF-780

# reliable

Compact Laser Fax

- 3-Second Super G3 Fax Transmission
- 2.8-Second High-Speed Scanning
- Quick Memory Transmission
- Triple-Access Multi-Tasking Capability
- 120-Page Standard Memory/Expandable Up To 760 Pages



**Panasonic**  
**ideas for life**

## Features

- Auto Dialer
  - One-Touch: up to 32 stations
  - Abbreviated: up to 100 stations
  - Telephone Number Digits : up to 36
- Program Keys
  - (up to 4 Programs)
- Multi-Tasking Operation
- Directory Search Dialing
- Directory Sheet Print
- Intelligent Redial
- Chain Dialing
- Distinctive Ring Detector (DRD)
- Quick Memory Transmission
- Multi-Station Transmission
  - (up to 144 stations)
- Automatic Memory Retransmission
- Deferred Transmission
- Deferred Multi-Station Transmission
- Priority Direct Transmission
- Edit File Mode with View Mode
- Automatic Cover Sheet
- Receive to Memory
- Substitute Reception
- Selective Reception
- Number of Memory Job Files : Max. 10
- Fax Forward
- Polling/Multi-Station Polling
- Deferred Polling/Deferred Multi-Station Polling (up to 144 stations)
- Memory Polling Transmission (1 file)
- Confidential Mail Box\*<sup>1</sup>
- Password Transmission/Reception\*<sup>1</sup>
- ITU-T Sub-Address Transmission
- Panasonic Super Smoothing (Fax/Copy)
- 64-Level Halftone
- Automatic/Fixed Reduction
- Overlapping Print
- Collation Stack
- Verification Stamp
- Communication Journal with Image Data
- Header/Total Page Print
- Transaction Journal with View Mode
- Fax Access Code (Fax Lock)
- PIN Code Access
- Fax/Telephone Auto Switch
- External TAM Interface
- Remote Reception
- Multi-Purpose LCD Display (20 x 2 lines)
- Multiple Copy with Sorting
  - (up to 99 copies)
- Reduction Copy
- Energy Saver
- Remote Diagnostic
- Check & Call Function

## Control Panel



## Options

- 2 1/4 MB Flash Memory Cards (UE-410046F/UE-410047F/UE-410048F)
- Handset Kit (UE-403176)

## Consumables

- All-In-One Toner Cartridge (toner/developer/drum) (UG-5510)
- Approx. 9,000-page Toner \*<sup>9</sup>

## Dimensions



## UF-780 Specifications

Compatibility	ITU-T Group 3, ECM
Modem Speed	33,600 - 2,400 bps with automatic fallback
Coding Scheme	MH/MR/MMR
Transmission Speed	Approx. 3 seconds / page* <sup>3</sup> (Letter)
Document Size	Max. 10.1" x 78.7" (257 mm x 2000 mm)(with operator's assistance) Min. 5.8" x 5.0" (148 mm x 128 mm)
Effective Scanning Width	8.35" (212 mm)
Automatic Document Feeder	50 sheets
Document Thickness	Single sheet: 0.0024" - 0.0060" (0.06 - 0.15 mm) Multi-sheet: 0.0024" - 0.0039" (0.06 - 0.10 mm)
Scanning Resolution (Fax)	Standard: 203 dots/inch x 98 lines/inch (8 dots/mm x 3.85 lines/mm) Fine: 203 dots/inch x 196 lines/inch (8 dots/mm x 7.7 lines/mm) Super Fine: 203 dots/inch x 391 lines/inch (8 dots/mm x 15.4 lines/mm) 406 dots/inch x 391 lines/inch* <sup>4</sup> (16 dots/mm x 15.4 lines/mm)
Scanning Speed	Approx. 2.8 second/page (Letter, Standard mode)* <sup>5</sup>
Recording Method	Laser printing on plain paper
Recording Speed	6.5 pages per minute* <sup>6</sup>
Recording Paper Size	Letter / Legal / A4 cut sheet on plain paper
Effective Recording Width	8.2" (208 mm)(Letter)
Recording Paper Capacity	250 sheets (Using 20 lb paper)
Recording Resolution	Fax / Copy 406 dots/inch x 391 dots/inch
Image Memory Capacity	Approx. 120 pages* <sup>7</sup>
Optional Memory Card	Base Memory plus approx. 160/320/640 pages* <sup>7</sup>
Power Requirements	108 - 132 V AC 47 - 63 Hz Single phase
Power Consumption	Standby (Sleep Mode : On) : 1.2 Wh Max.: Approx. 470 W
Dimensions (W x D x H)	14.6" x 18.0" x 9.8" (370 mm x 457 mm x 250 mm)* <sup>8</sup>
Weight	20 lb (9.0 kg)* <sup>8</sup> (Excluding consumable supplies and optional equipment)

\*<sup>1</sup> Panafax proprietary features work only with selected Panafax machines.

\*<sup>2</sup> Based on ITU-T Image No. 1 scanned in multiple copy mode, set on fine resolution and using letter size recording paper. Yield may vary according to operating conditions and environment where the machine is installed.

\*<sup>3</sup> Transmission time applies to memory transmission of text data using only ITU-T Image No. 1 between the same models at maximum modem speed. Transmission time may vary in actual usage. Usually public telephone lines can only support communications speeds of 28.8 kbps or lower. Via PBX, transmission speed may fall back to a lower speed.

\*<sup>4</sup> Interpolated resolution (Optical Resolution: 203 dots/inch x 391 lines/inch)

\*<sup>5</sup> Scanning speed applies to the feeding process from the top to the end of a single page test chart. The time for the feeding process does not include the time that it takes for the top edge of the page to reach the scanning point and page ejection. Time for entire storing process is not applied.

\*<sup>6</sup> In multiple copy mode excluding the first copy.

\*<sup>7</sup> Based on ITU-T Image No. 1 scanned in Standard mode.

\*<sup>8</sup> Dimensions and weight are approximate.

\*<sup>9</sup> ITU-T Image No.1 chart printed in multiple copy mode(20°C, 50%RH).

Super G3 is the classification given to a type of facsimile that conforms to the 33.6 kbps transmission method standardized in accordance with ITU-T V.34 recommendations.

ENERGY STAR® is a U.S. registered mark.

All other brand or product names are the property of their respective holders.

Design and specifications are subject to change without notice.

## ISO 9001 Quality Management System

Our business processes which produce document, information and network products, from manufacturing to marketing, conform to ISO9001 Quality Management System standard.

Design, development, manufacture, installation, repair and maintenance of document, information and network products, their associated devices and consumables.

In addition, the plants outside Japan have acquired ISO 9001 certification.



# Panasonic®

Panasonic Digital Document Company

Unit of Matsushita Electric Corporation of America

Two Panasonic Way, Secaucus, NJ 07094

For a local dealer, please call 1-800-742-8086

http://www.panasonic.com/office

FAX-780-SS